

SEALING COMPOUND

COMPOUND-A FIBER-X



A-10



A-05



X-02



X-01



sermatex

REV.16 / 15.04.2026

p. 1 de 2

SEALING COMPOUND

Technical data

ESPECIFICAÇÕES

MARKING

Ex

AREA OF APPLICATION

Zone 1
Zone 2
Groups IIA IIB and IIC

APPROVALS

IEC 60079-0 (General Requeriments)
IEC 60079-1 (Flameproof)

CERTIFICATE OF CONFORMITY

Segurança



OCP 0034



INMETRO

INMETRO

NCC 24.0129 U

APLICAÇÕES

COMPOUND-A APPLICATION :

Used to seal fitting in flameproof enclosures IIA/IIB/IIC.
Used together with Fiber-X.

FIBER-X APPLICATION :

Fibrous auxiliary material to use with Compound-A.

CHARACTERISTICS

COMPOUND-A CHARACTERISTICS:

Supplied in powder form ready to be mixed with water for curing. Packaged in a waterproof bucket that can be used for preparing of compound. Inside the packaging, there is a spatula.
Volumetric Efficiency: 1,176 g/cm³. Setting time: 45-60 minutes. - Curing time: 432 hours.

FIBER-X CHARACTERISTICS :

Fibrous compound supplied in flakes and used to hold Compound-A in place while curing. Supplied in waterproof buket
Volume Efficiency: 0,175g/cm³.

ORDENING CODE

COMPOUND-A

Packing with 500g = cod.: A-05
Packing with 1000g = cod.: A-10

FIBER-X

Packing with 0,1Kg = cod.: X-01
Packing with 0,2Kg = cod.: X-02